

REPORT DC

AD-A237 017

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters of the Office of Management and Budget, Paperwork Project (0704-0188).

Instructions: Search for existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters of the Office of Management and Budget, Paperwork Project (0704-0188).

1 AGENCY USE ONLY (Leave blank)

2 REPORT DATE

May 1991

REPORT TYPE AND DATES COVERED

Professional Paper

4 TITLE AND SUBTITLE

MODELING A SHIPBOARD FAN ANTENNA

6 AUTHOR(S)

L. Koyama

5 FUNDING NUMBERS

PR: CHB2
WU: DN307346
PE: 0602232N

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Naval Ocean Systems Center
San Diego, CA 92152-50008. PERFORMING ORGANIZATION
REPORT NUMBERApproved for
Distribution
GHS-1

9 SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Naval Ocean Systems Center
Block Programs
San Diego, CA 92152-500010 SPONSORING/MONITORING
AGENCY REPORT NUMBER

Justification

11. SUPPLEMENTARY NOTES

By
Distribution

Availability

Availability

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

DISTRIBUTION CODE

QUALITY
INSPECTED
1

A-1

13. ABSTRACT (Maximum 200 words)

In the frequency range for which US Navy shipboard fan antennas are designed, 2-6 MHz, the whole ship is in fact the antenna. This makes for a very large and complex numerical modeling problem. This paper describes an effort concentrated on a destroyer, the *Spruance* (DD-963), for which NOSC has a 1/48 scale brass model to make measurements on for comparison with the calculations. The antenna characteristics used for judging the accuracy of the numerical model with regards to measured data were the feedpoint impedance and the voltage across the insulator at the apex of the fan.

NEC-3-VLF was used on a 719 segment model. To make a good comparison between measured and calculated data, the code was run for 51 frequencies between 1.5 and 6.5 MHz. The computer used was a Convex C210 which has close to the performance of a single processor on the Cray X/MP-48. The code was compiled to take advantage of the vector architecture of the Convex and its 64 bit word size.

There was a very good match between the antenna characteristics of the numerical model and the measurements from the brass model, showing NEC to be a viable tool for modeling a complex structure with reasonable engineering effort and use of computer resources.

Published in *Proceedings of the 7th Annual Review of Progress in Applied Computational Electromagnetics*, Mar 1991.

14 SUBJECT TERMS

communications countermeasures
C³CM
EW

15 NUMBER OF PAGES

16 PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT

UNCLASSIFIED

18 SECURITY CLASSIFICATION
OF THIS PAGE

UNCLASSIFIED

19 SECURITY CLASSIFICATION
OF ABSTRACT

UNCLASSIFIED

20 LIMITATION OF ABSTRACT

SAME AS REPORT

UNCLASSIFIED

21a NAME OF RESPONSIBLE INDIVIDUAL L. Koyama	21b TELEPHONE (include Area Code) (619) 553-3784	21c OFFICE SYMBOL Code 824

MODELING A SHIPBOARD FAN ANTENNA

Lance Koyama
Code 824
Naval Ocean Systems Center
San Diego, CA 92152

Abstract

In the frequency range for which US Navy shipboard fan antennas are designed, 2-6 MHz, the whole ship is in fact the antenna. This makes for a very large and complex numerical modeling problem. This paper describes an effort concentrated on a destroyer, the Spruance (DD-963), for which NOSC has a 1/48 scale brass model to make measurements on for comparison with the calculations. The antenna characteristics used for judging the accuracy of the numerical model with regards to measured data were the feedpoint impedance and the voltage across the insulator at the apex of the fan.

NEC-3-VLF was used on a 719 segment model. To make a good comparison between measured and calculated data, the code was run for 51 frequencies between 1.5 and 6.5 MHz. The computer used was a Convex C210 which has close to the performance of a single processor on the Cray X/MP-48. The code was compiled to take advantage of the vector architecture of the Convex and its 64 bit word size.

There was a very good match between the antenna characteristics of the numerical model and the measurements from the brass model, showing NEC to be a viable tool for modeling a complex structure with reasonable engineering effort and use of computer resources.

91 6 11 004

91-01716

